

TECHNICAL SHEET

Capacity	680 cc
Top Out	203 x 110
Top In	186 x 93
Base	160 x 68
Useful Height	49
Total Height	59
Net Weight	9,90
Model	CH (2)
Gauge	65
Alloy (*0)	8006 H24/3003 H24
Lubrication	(1)
Holes	NO
Diameter	
Colors in/out	ALU/ALU
Rolled edge	2,4 mm
Temperature	-40°C - 350°C

CH0700 10 x 100

#Pcs pro carton:	1000
#Pcs pro bag	100
#Bags pro carton	10
#Cartons pro palette	24
#Cartons pro layer	6
#Layers Pro palette	4
#Pcs pro palette	24000
Carton dimension L.D.H	430 x 355 x 475 mm
Tare carton (kg)	0,68
Net carton (kg)	9,90
Gross carton (kg)	10,58
Gross palette (kg)	283,92
Palette height (meter)	2,05
Country of Production	(9)

Welvaartstraat 14-B2200 HERENTALS

EAN code Bag	5410797300521
EAN code cart./Technifil	5410797300514
EAN code Palet	



FOR DETAILED INFORMATION CONSULT our: "Declaration of Conformity for Aluminium Foil Containers and Lids"

Made of materials that complies with :

- * Regulation **2004/1935/EC** on material and articles intended to come into contact with food and 2023/2006/EC on Good Manufacturing Practices.
- * European Standard **EN602:2005** "Aluminium and aluminium alloys-Wrought products - Chemical Composition of semi products used for the fabrication of articles for use in contact with food and EN573-3:2014 "Aluminium and aluminium alloys- chemical composition"
- * Belgium: Royal Decree 12 June 2017 adapting Royal Decree 11 Mai 1992 on FCM.
- * France: Arrête du 17/8/1987 relatif aux matériaux et objets en aluminium ou en alliages d'aluminium au contacts des denrées, produits et boissons alimentaire ; DGCCRF document DM/4B/COM/001, fiche MCDA n°2B, version 1/1/2016
- * Netherlands : « Warenwetregeling verpakking en gebruiksartikelen », 328583-11560-VGP.
- * Product is free of GMO, allergens, nanoparticles, Bisphenol A and are of non-animalorigin.

Proper conditions of transport, storage and use:

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- * Avoid moisture (wetness, condensation, ...).
- * Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms. Open packaging 2-3 hours prior to use.
- * Aluminium tray can be used within temperature range : -40°C / +350°C (max 60 min). However, content of filled containers can influence these limits. Always remove lid before putting it into the oven.
- * It is recommended to avoid contact with strongly acidic and/or alkaline products and salty foods. Uncoated aluminium foil containers are not cooking utensils and boiling of aqueous solutions at 100°C should be limited to maximum 1 hour.
- * The suitability of uncoated aluminium foil containers for specific applications should be ascertained by the relevant user/customer/packer.

Tolerances :

**thickness (EN546-3) and weight +/- 8%
dimensions +/- 1 mm pro side**

- (0) Or equivalent
- (1) Lubricant approved for food contact, the amount used depends on the shape and complexity of the tray
- (2) Rectangular model with vertical edge
- (3) Rectangular approved model with rolled edge
- (4) Round model with vertical edge
- (5) Round Model with rolled edge
- (6) Lid Aluminium
- (7) Smooth Wall
- (8) Special forms
- (9) Produced in Belgium by Aluvin
- (10) Produced in Europe for Aluvin

