

TECHNICAL SHEET

Volume	0
Top Out	120x105 mm
Top In	0 mm
Base	150x134 mm
Useful Height	26 mm
Total Height	26 mm
Net Weight	8,00 g
Model	LP (2)
Gauge	220 µ
Alloy (*0)	RPET (0)
Lubrication	0
Holes	NO
Diameter	
Colors in/out	
Rolled edge	0
Temperature	-20°C-40°C

LP-WC0515-12X50

Welvaartstraat 14-B2200 HERENTALS

EAN code Bag	5,4108E+12
EAN code cart./Technifil	5,4108E+12
EAN code Palet	



#Pcs pro carton:	600
#Pcs pro bag	50
#Bags pro carton	12
#Cartons pro palette	20
#Cartons pro layer	4
#Layers Pro palette	5
#Pcs pro palette	12000
Carton dimension L.D.H	600x400x425mm
Tare carton (kg)	1,00
Net carton (kg)	4,80
Gross carton (kg)	5,80
Gross palette (kg)	146,00
Palette height (meter)	2,28
Country of Production	(10)

FOR DETAILED INFORMATION CONSULT our: "Declaration of Conformity (R) PET LIDS" _ www.aluvin.be

Made of materials that complies with :

- * Regulation 1935/2004/EC on material and articles intended to come into contact with food and 2023/2006/EC on Good Manufacturing Practice.
- * Regulation 10/2011/EC on plastic materials and articles intended to come into contact with food.
- * Regulation 94/62/EC on packaging and packaging waste. With regard to the contents of heavy metals, the provisions of Directive 94/62 EC (including the amendment Directives 2004/12 EC and 2005/20 EC) are adhered to.
- * The PET lids correspond to the current Version of Directive (EG) Nr. 1907/2006. It is assured that no high concern materials as part of the Version of Directive (EG) Nr. 1907/2006 are included. Based on the valid "Candidate List of Substances of Very High Concern" (SVHC-List).
- * Product is free of GMO, allergens, nanoparticles, Bisphenol A and are of non-animalorigin.
- * Belgium: Royal Decree 12 June 2017 adapting Royal Decree 11 Mai 1992 on FCM.
- * Netherlands : « Warenwetregeling verpakking en gebruiksartikelen », 328583-117560-VGP.

Proper conditions of transport, storage and use:

- * Long-term storage at 5-40°C in an atmosphere as dry as possible. Avoid moisture (wetness, condensation,..)
- * **ATTENTION : Not convenient for use in microwave/oven - remove lid from container before heating container in oven/microwave**
- * Suitable for storage in refrigeration: minus -20°C. Common use Temp° range: -20°C till +40°C (max 15 minutes)
- * Temperature of softening: 70°C

Tolerances :
thickness and weight +/- 8%
dimensions +/- 1,5 mm

- (0) Or equivalent*
(1) Lubricant approved for food contact, the amount used depends on the shape and complexity of the tray.
(2) Rectangular model
(3) Round model

- (9) Produced in Belgium by Aluvin*
(10) Produced in Europe for Aluvin

Version 10
Creation date: 18/04/2021
Expiry date: 17/04/2024
or by next version – see: www.aluvin.be

